

Features and Advantages:

Facilitates insertion of sanitary fittings.

Precision Controlled ID and OD Dimensions –

• Food Grade Materials - Hose complies with

complies with applicable USDA<sup>(12)</sup> requirements.

applicable FDA<sup>(03)</sup> and 3-A<sup>(01)</sup> requirements. Hose





- "Cold-Flex" Materials (MILK-LT only) Hose remains flexible in severe sub-zero temperatures.
  - **Transparent Construction –** "See-the-flow." Allows for visual confirmation of material flow.
  - **Smooth Outer Cover** Provides increased pressure rating and smooth surface for banding.
  - Phthalate Free

Nominal Specifications											
Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending	Standard	Mainha
	(in)	(mm)	(in)	(mm)	68°F	104°F	68°F	104°F	Radius at 68°F (in)	Length (ft)	Weight (lbs/ft)
MILK150	1-1/2	38.1	1.79	45.5	75	50	Full	26	4	100	0.45
MILK200	2	50.8	2.33	59.2	75	50	28	25	6	100	0.63
MILK250	2-1/2	63.5	2.87	73.0	55	40	28	24	10	100	0.81
MILK300	3	76.2	3.42	86.9	55	40	28	24	11	100	1.18
MILK-LT150	1-1/2	38.1	1.79	45.5	75	50	Full	26	4	100	0.45
MILK-LT200	2	50.8	2.33	59.2	75	50	28	25	5	100	0.65
MILK-LT250	2-1/2	63.5	2.87	73.0	55	40	28	24	8	100	0.84
MILK-LT300	3	76.2	3.42	86.9	55	40	28	24	11	100	1.20

**NOTE:** Service life may vary depending on operating conditions and type of material being conveyed. **NOTE:** For details of the following compliances, refer to footnotes listed on page 63.

\*Actual service temperature range is application dependent.

**3A**<sup>(01)</sup>, **BSE/TSE**<sup>(02)</sup>, **FDA**<sup>(03)</sup>, **Phthalate Free**<sup>(10)</sup>, **RoHS**<sup>(11)</sup>, **USDA**<sup>(12)</sup>

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.